



■ MN60



■ Y7N



■ Ci60



■ D38N



■ E3N



■ PAC12



■ PAC22

	AC				AC / DC			
	■ Ci60	■ D38N	■ MN60	■ Y7N	■ E3N	■ PAC12	■ PAC22	
Measurement range	0.1 to 30 A peak 0.1 to 300 A peak 1 to 2000 A peak	1 to 90 A peak 1 to 900 A peak 1 to 9000 A peak	0.1 to 60 A peak AC 0.5 to 600 A peak AC	1 A to 1200 A peak	0.05 to 10 A peak 1 to 100 A peak	0.2 to 60 A peak 0.4 to 60 Adc 0.5 to 600 A peak 0.5 to 600 Adc	0.2 to 150 A peak 0.4 to 150 Adc 0.5 to 1400 A peak 0.5 to 1400 Adc	
Transformation ratio	10 A / 1 V 100 A / 1 V 1 kA / 1 V	1 A / 10 mV 1 A / 1 mV 1 A / 0.1 mV	1 A / 100 mV 1 A / 10 mV	1A / 1 mV	1 A / 100 mV 1 A / 10 mV	1 A / 10 mV 1 A / 1 mV		
Bandwidth	10 Hz to 100 kHz	30 Hz to 50 kHz	40 Hz to 40 kHz	5 Hz to 10 kHz	DC - 100 kHz	DC - 10 kHz		
Accuracy	3 %, 2 %, 1 %	≤2 %	≤2 % and 1.5 %	≤2 %	3 % 4 %	≤1.5 % ≤2 %	≤1.5 % ≤2 %	
Clamping diameter	52 mm	64 x 150 mm	20 mm	max 30 mm or 30 x 63 mm	11.8 mm	30 mm	39 mm	
Input	AC				AC/DC			
Cable length	2 m	2 m	2 m	2 m	2 m	1.5 m	2 m	
Dimensions (overall)	216 x 111 x 45 mm	310 x 120 x 48 mm	135 x 51 x 30 mm	213 x 66 x 34 mm	231 x 67 x 36 mm	224 x 97 x 44 mm	236.5 x 97 x 44 mm	
Weight	550 g	1200 g	180 g	420 g	330 g	440 g	520 g	
Power supply							1 battery 9 V	

To choose a model: see page 46
 Technical specifications: see table pages 48 and 49